



CITY OF PINOLE

PUBLIC WORKS DEPARTMENT

2131 Pear Street
Pinole, CA 94564

Phone: (510) 724-9010
FAX: (510) 724-9826
www.ci.pinole.ca.us

Grading Permit Application

| | | | | |
|---|-----------------------|------------------|-----------------------|--------------------------------|
| Job Address: | | | | |
| APN: | | | Lot Acreage: | |
| Detailed Description of Proposed Work: | | | | |
| | Property Owner | Applicant | Civil Engineer | Geotechnical Consultant |
| Name: | | | | |
| Address: | | | | |
| City: | | | | |
| State, ZIP | | | | |
| Phone: | | | | |
| Email: | | | | |
| Fax: | | | | |

| | |
|--|-----------------------------------|
| Project Information | |
| Proposed Work Start and Finish Dates: | |
| Approximate Area of Disturbance (Square Feet or Acres): | |
| Estimated Cut Quantity (CY): | Estimated Cut Depth (FT): |
| Estimated Fill Quantity (CY): | Estimated Fill Depth (FT): |
| Import Volume (CY): | Export Volume (CY): |
| If creating a reservoir, Estimated Storage (AC-FT): | |
| Location of fill or disposal sites of excavated material if other than on site of excavation: | |

Grading Plan Requirements:

- A. The grading plans, 24" x 36" prepared and signed by a civil engineer shall contain the following information.
 - 1) A vicinity map showing the location of the work.
 - 2) The property line boundary of the site.
 - 3) All existing improvements on and adjacent to the property.
 - 4) The existing and proposed contours of the site. The minimum contour interval shall be one foot or less for slopes five percent or flatter, and five feet or less for slopes steeper than five percent. The contour interval shall be small enough to clearly show the drainage pattern of the site.
 - 5) The existing and proposed drainage.
 - 6) The extent and manner of the cutting of trees and the clearing of vegetation, the disposal of same, and the measures to be taken for the protection of undisturbed trees and vegetation, unless this information is shown on an erosion and sediment control plan.
 - 7) Any other information required by the director of public services.
- B. Runoff calculations must be submitted with the grading plan.
 - 1) Maximum runoff shall be computed using the rational method. The rainfall intensity-duration curve contained in the Pinole 5-year Facility Plan, Dated 1975, or a similar curve approved by the director of public services shall be used in the computation.
 - 2) Runoff design shall accommodate the full and anticipated future development within the drainage area.
 - 3) Drainage channels having a drainage area of four-square miles or more shall be designed to contain a fifty-year frequency of occurrence runoff. Drainage channels having a drainage area of less than four square miles and more than one square mile shall be designed to contain a twenty-five-year frequency of occurrence runoff. Drainage channels having a drainage area of one square mile or less shall be designed to contain a ten-year frequency of occurrence runoff.
- C. The maximum size of each sheet of the grading plan shall be 24" by 40".
- D. The scale of the grading plan shall be an engineering scale large enough to show clearly all details, but not less than one-inch equals one hundred feet.
- E. The details of any drainage structures or retaining walls must be shown on the grading plan.
- F. Specifications describing proposed construction methods and materials to be used must be submitted with the grading plan.
- G. The grading plan must be signed by a registered civil engineer and must be prepared under his or her direction.
- H. An estimate of the cost of accomplishing the work described and delineated on the grading plan and the permit must be submitted in a form which is acceptable to the Public Works Director.

Erosion and Sediment Control Plan:

- A. A final erosion and sediment control plan, prepared by a registered civil engineer, shall be submitted unless all of the following conditions are met:
 - 1) The site is less than one-quarter of an acre in area and there is less than one hundred fifty cubic yards of excavation or fill;
 - 2) The provisions for runoff control are in accordance with the provisions of this chapter and are acceptable to the director of public services;
 - 3) The average slope of the site before grading is less than fifteen percent;
 - 4) The proposed grading does not pose a threat to adjacent or downstream properties as determined by the director of public services;
 - 5) The proposed grading does not obstruct drainage channels;

- 6) The proposed grading is deemed to have no significant environmental impact as determined pursuant to the provisions of the California Environmental Quality Act, as amended, and the regulations promulgated by the California Resources Agency and the Pinole city council to implement said Act.
- B. The final erosion and sediment control plan must effectively minimize soil erosion and sedimentation from the completed project site and must also provide for the control of runoff from the site.
 - C. The final and interim erosion and sediment control plans shall contain the following information:
 - 1) A description and delineation of the vegetative measures to be taken to minimize erosion and sedimentation.
 - 2) A description and delineation of the temporary and permanent measures to be taken to protect manufactured or disturbed slopes from erosion by mechanical means such as with mulches, diversion dikes, etc.
 - 3) The delineation of the drainage control measures to be taken which shall include surface runoff and sediment yield calculations.
 - 4) The extent and manner of the cutting of trees and the clearing of vegetation, the disposal of same, and the measures to be taken for the protection of undisturbed trees and vegetation.
 - 5) The methods to be used for the disposal of excess materials.
 - 6) The methods to be used for the control of dust.
 - 7) A description and delineation of the temporary and permanent measures to be taken to retain sediment on the site.
 - 8) A description of the measures to be taken to maintain the devices shown on the plan during grading operations and construction on the site.
 - 9) The extent of disturbed ground that will exist, what streets will be paved, and what drainage devices will be installed prior to the start of each rainy season.
 - 10) Any other information required by the director of public services.
 - 11) Schedule for installation and maintenance of erosion and sediment control measures.
 - D. The Erosion and Sediment Control Handbook should be used as a guide as to what measures should be taken for any particular set of circumstances.
 - E. An interim erosion and sediment control plan is required prior to each rainy season during construction for a project for which a final erosion and sediment control plan is required by this chapter. The city will determine by July 15th if an interim plan will be necessary and on what stage of project completion the plan shall be based. The plan must be submitted in a timely manner thereafter to allow the city to review and approve the plan prior to September 1st. The measures delineated and described in the plan must be operational prior to October 1st.
 - F. An estimate of the cost of accomplishing the work described and delineated on the final and interim erosion and sediment control plans and the permit must be submitted in a form which is acceptable to the director of public services.
 - G. Rainy season work may be authorized by the public services director if erosion and sediment control measures are installed and functioning.

Time Schedule:

The time schedule shall define the staging of the work, including the construction and implementation of the facilities shown on the grading plan and the interim and final erosion and sediment control plan.

Signature:

I hereby authorize employees, agents, and/or consultants of the City of Pinole to enter upon the subject property upon reasonable notice, as necessary, to inspect the premises and process this application. I understand that in cases where the development site is large or cannot be easily seen or accessed from the nearest public road, the Department of Public Works may determine that a publicly noticed site inspection by the decision maker is necessary. In this instance, I hereby authorize the conduct of such inspections of the premises upon reasonable notice.

I hereby authorize the Department of Public Works to reproduce plans, reports, and exhibits as necessary for the processing of this application. I understand that this may include circulating copies of the reduced plans and supporting documentations/reports for public inspection. Multiple signatures are required when plans are prepared by multiple professionals.

I hereby certify I agree to do work in accordance with City of Pinole Municipal Code §15.36 Excavation, Grading and Earthwork Construction and the rules, regulations, and general/special conditions of the City of Pinole Department of Public Works Department subject to its inspection and approval.

I hereby certify I have read this application form and to the best of my knowledge, the information in this application form and all the exhibits are complete and accurate. I understand any misstatement or omission of the requested information or of any information subsequently requested shall be grounds for rejecting the application, deeming the application incomplete, denying the application, suspending, or revoking a permit issued on the basis of these or subsequent representations, or for the seeking of such other and further relief as may seem proper to the City of Pinole. I declare under penalty of perjury under the laws of the State of California the foregoing is true and correct.

Applicant Signature

Print Name

Date

Property Owner Signature

Print Name

Date

Property Owner Signature

Print Name

Date

Property Owner Signature

Print Name

Date

Civil Engineer Signature

Print Name

Date

Contractor Signature

Print Name

Date

N.P.D.E.S Compliance Certification

As the _____, of the project, I have reviewed the *Best Management Practices*
Applicant Role

Handbooks, California Storm Water Quality Task Force, Sacramento, CA, and have proposed the implementation of the Best Management Practices (BMPs) applicable, to effectively minimize the negative impact of this project construction activities on the surrounding water quality. The selected BMPs will be installed, monitored, and maintained to ensure their effectiveness. The BMPs that I have not chosen for implementation are redundant or deemed not applicable to the proposed construction activities. If at any time, site conditions and/or the County official warrant reevaluation and revisions the chosen BMPs, the appropriate changes will be made without unnecessary delay. I am aware that failure to properly implement and maintain, while under construction, the BMPs necessary to prevent the discharge of pollutants from the project could result in significant penalties and / or delays.

Signature: _____

Date: _____

Print Name: _____

Project Description:

| |
|--|
| |
|--|

Project Address: _____

Indemnification and Hold Harmless Agreement

Contractor Name: _____

To the fullest extent permitted by law, Contractor shall indemnify, defend with counsel acceptable to City, and hold harmless City and its officers, elected officials, employees, agents, and volunteers (collectively, “Indemnitees”) from and against any and all liabilities, losses, damages, claims, expenses, and costs of every nature, including reasonable attorney’s fees (collectively, “Liability”) arising out of or in connection with Contractor’s work under the encroachment permit issued pursuant to this application, or its failure to comply with any of the requirements contained in such encroachment permit, except to the proportionate extent that the Liability is caused by the negligence or willful misconduct of the City. Contractor’s indemnification obligations shall survive the termination of the encroachment permit.

Authorized Representative’s Name & Title: _____

Signature: _____

Date: _____